



	Expansion	1*PCI-e X16, 1*PCI-e X4, 2*PCI
	GPIO	1*2×5 Pin 2.0mm GPIO, Supports four inputs and four outputs
	OS system	Windows 7/10; Linux Centos/Ubuntu
<b>CES-585A</b>	CPU	Intel® Core 4th Gen CPU, i3/i5/i7, LGA 1150, Intel B85
	Memory	4*DIMM RAM, DDR3 1066/1333/1600MHZ, 32GB Max
	Storage	4*STATIII, 1*mSATA
	I/O ports	USB: 4*USB3.0; 8*USB2.0
		COM: 6*RS232, 4*RS485
		Display: 1*VGA, 1*VGA
		1*LPT, 1*PS/2
	Network(LAN)	2* Intel I211 10/100/1000Mbps Ethernet
	Expansion	1*PCI-e X16, 1*PCI-e X4, 2*PCI
GPIO	1*2×5 Pin 2.0mm GPIO, Supports four inputs and four outputs	
OS system	Windows 7/10; Linux Centos/Ubuntu	
<b>CES-586A</b>	CPU	Intel® Core 6-9th Gen CPU, i3/i5/i7, LGA 1151, Intel H110
	Memory	2*DIMM RAM, DDR4 2133/2400/2666MHZ, 32GB Max
	Storage	3*STATIII, 1*mSATA
	I/O ports	USB: 4*USB3.0; 6*USB2.0
		COM: 8*RS232, 2*RS485
		Display: 1*HDMI, 1*VGA
		1*LPT, 1*PS/2
	Network(LAN)	2* Intel I211 10/100/1000Mbps Ethernet
	Expansion	1*PCI-e X16, 1*PCI-e X4, 2*PCI
GPIO	1*2×5 Pin 2.0mm GPIO, Supports four inputs and four outputs	
OS system	Windows 7/10; Linux Centos/Ubuntu	
<b>ATX-809</b>	CPU	Intel® Core 12-13th Gen CPU, i3/i5/i7/i9, LGA 1700, Pentium processor, Intel H610
	Memory	2*DIMM RAM, DDR4 2133/2400/2666MHZ, 64GB Max
	Storage	4*STATIII+1*M.2
	I/O ports	USB: 2*USB3.2; 2*USB3.0; 6*USB2.0
		COM: 6*RS232, 2*RS485/ 2*RS422 optional
		Display: 1*HDMI, 1*VGA, 1*DP
		1*LPT, 1*PS/2, 1*TMP2.0
	Network(LAN)	2* Intel I211 10/100/1000Mbps Ethernet
	Expansion	1*PCI-e X16, 1*PCI-e X4, 2*PCI-e X1, 3*PCI
Watch dog	support watch dog, Supports system restart in 1 to 225 seconds	
GPIO	1*2×5 Pin 2.54mm GPIO, Supports four inputs and four outputs	
OS system	Windows 10/11; Linux Centos/Ubuntu	

