

- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor

► Introduction



The UPC-302F industrial PC showcases a fanless embedded design , equipped with 12th Gen Core™ i3/i5/i7 processors, delivering superior performance. **Based on CESIPC LEGO-mode, the UPC-302F, with 14 USB ports**, is ideal for airport systems, kiosks, POS, smart manufacturing, and lab automation. It supports multiple peripherals like scanners, cameras, and touchscreens, ensuring high integration and efficiency.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance
- ★ i-Door Technology for Efficient, Tailored Solutions

- ★ LEGO MODE with Customizable Function Cards
- ★ 14xUSB Ports for Extensive Peripheral Expansion

► Specifications

System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

Wireless Communication

Wi-Fi	Intel 8260AC NGW dual-band Gigabit 5G M2 wireless network card 4.2 Bluetooth 2.4G / 5G
Wireless Network	/

- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor

I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0	10	10	10	10	10	10	10	10
USB 3.0	4	4	4	4	4	4	4	4
RS232	3	3	3	3	3	3	3	3
RS485	1	1	1	1	1	1	1	1
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

Mechanical

Dimension	300 (W) × 160 (D) × 50 (H) mm
Cutout Size	337 (W) × 160 (D) × 53.2 (H) mm
Weight	3.7KG G.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical	Aluminum Extrusion + Sheet Metal
Construction	Structure
Mount	Bracket Mount / VESA Mount

Environmental

Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing
EMC	CE, FCC (According to EN 55032 & EN 55035)
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

OS

Windows	Windows 10 / 11
Linux	Ubuntu 22.04


► Product Images




► Applications

- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor



► Product Sizes



- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor

► Product Selection

NO.	Model	Product Part Number	Describe Information	Standard Memory	Standard Storage
1	UPC-306F		Intel® Celeron® Processor J1900 Processor	4GB	SSD 128GB
2	UPC-307F		Intel® Celeron® Processor J6412 Processor	8GB	SSD 256GB
3	UPC-309F		Intel® Core™ i3-10110U Processor	8GB	SSD 256GB
4	UPC-309F		Intel® Core™ i5-10210U Processor	8GB	SSD 256GB
5	UPC-309F		Intel® Core™ i7-10510U Processor	8GB	SSD 256GB
6	UPC-302F		Intel® Core™ i3-1215U Processor	8GB	SSD 256GB
7	UPC-302F	C8.03.05.008	Intel® Core™ i5-1235U Processor	16GB	SSD 256GB
8	UPC-302F		Intel® Core™ i7-1250U Processor	8GB	SSD 256GB

Note: CPU model may vary. Contact sales for details