

- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor

► Introduction



The EPC-302E industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers four Gigabit LAN ports, equipped with Intel® 12th Gen. core i3/i5/i7 processor, delivering superior performance. Engineered for reliability, the EPC-302E ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored Solutions

► Specifications

System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor

I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0	5	4	2	2	2	2	2	2
USB 3.0	1	2	4	4	4	4	4	4
RS232	4	4	4	4	4	4	4	4
RS485	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	4 x Intel I210	4 x Intel I210	4 x Intel I210	4 x Intel I210	4 x Intel I210	4 x Intel I210	4 x Intel I210	4 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

Mechanical

Dimension	337.0 (W) × 160.0 (D) × 47.5 (H) mm
Installation dimensions	327.0 (W) × 100.0 (D)
Weight	2.3 KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical	Aluminum Extrusion + Sheet Metal
Construction	Structure
Mount	Bracket Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

Environmental

Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing
EMC	CE, FCC (According to EN 55032 & EN 55035)
Factory	EN IEC 61000-3-2
ODM	ISO9001: 2015
MTBF	BIOS / Boot on LOGO / OEM 60,000 Hours

► Product Images




- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor


► Applications



► Product Sizes



► I/O



- Intel® Celeron® Processor J1900
- Intel® Celeron® Processor J6412

- Intel® Core™ 10th Processor
- Intel® Core™ 12th Processor

► Product Selection

NO.	Model	Product Part Number	Describe Infomation	Standard Memory	Standard Storage
1	EPC-306E		Intel® Celeron® Processor J1900 Processor	4GB	SSD 128GB
2	EPC-307E		Intel® Celeron® Processor J6412 Processor	8GB	SSD 256GB
3	EPC-309E		Intel® Core™ i3-10110U Processor	8GB	SSD 256GB
4	EPC-309E		Intel® Core™ i5-10210U Processor	8GB	SSD 256GB
5	EPC-309E	C10.03.03.002	Intel® Core™ i7-10510U Processor	16GB	SSD 512GB
6	EPC-302E		Intel® Core™ i3-1215U Processor	8GB	SSD 256GB
7	EPC-302E		Intel® Core™ i5-1235U Processor	8GB	SSD 256GB
8	EPC-302E	C10.03.04.006	Intel® Core™ i7-1250U Processor	16GB	SSD 512GB

Note: CPU model may vary. Contact sales for details